

CLIENT: SunModo Corporation
14800 NE 65th Street
Vancouver, WA 98682

Project No: MED-1200c

Report Date: December 27, 2023

SAMPLE ID: Series: K50065-BK1 NanoBit Rafter Mount

SAMPLING DETAIL: The test sample manufactured by SunModo Corporation was submitted directly to QAI by the client. Samples were not independently selected for testing.

DATE OF RECEIPT: Samples were received at the QAI Miami Laboratory on October 18, 2023, and in good condition.

TESTING PERIOD: December 18, 2023

TESTING LOCATION: QAI Laboratories – Miami, Florida, USA

AUTHORIZATION: QAI proposal number 23MT09261 dated September 26, 2023, signed by Roland Jasmin, Director of Engineering of SunModo Corporation, dated October 2, 2023.

TEST PROCEDURE: Testing to the following requirements:

- TAS 100-23(A) Test Procedure for Wind and Wind Driven Rain Resistance and/or Increased Windspeed Resistance of Soffit Ventilation Strip and Continuous or Intermittent Ventilation System Installed at The Ridge Area

TEST RESULTS: The four samples of series: K50065-BK1 NanoBit Rafter Mount achieved passing results found on page 3 of this test report when tested in accordance with the TAS 100-23(A).

CONTENTS: Test report pages 1 through 18.

Prepared By

Lusinda Delgado

Lusinda Delgado
Technical Report Writer

Signed for and on behalf of
QAI Laboratories

Printed from an e-signed document

Digitally signed
by Jose Sanchez
Date:
2024.01.18
12:59:59 -05'00'

Jose Sanchez
Operation Manager

Page 1


THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Table of Contents	Page	Rev
Sample A-1		
Description of Test Sample	3	1
Test Results Sample A-1		
TAS 100(A)	3	
Pictures	4-11	
Conclusion	11	
Appendix A	12-16	
Appendix B	17	
Notes Table	18	
Remarks Table	18	
Revision Table	18	1

Technician:
Ian McGinley

W/E: Professional Engineer:
Idalmis Ortega, P.E.
FL License No. 76905



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



DESCRIPTION OF SAMPLE	
Model Designation:	Series: K50065-BK1 NanoBit Rafter Mount
Sample A-1	
Test Deck: Test deck was constructed by QAI Laboratory. The deck consisted of APA 32/16 span rated sheathing of 15/32" thickness Grade C-D with 3 ply installed over 2" by 6" perimeter supports and 2" by 6" intermediate supports spaced 24" apart. The sheathing was attached using 8d common nails at 6" on centers at panel edges and 12" on centers at intermediate supports. The test deck had a test slope of 2/12.	
Underlayment: The underlayment used on test deck consisted of self-adhering polystick IR-X	
Metal Flashing: One 2 1/2" by 2 1/2" by 26"-gauge galvanized metal flashing was installed at the perimeter of the deck over the underlayment and fastened using a staggered row of a 1 1/4" long corrosion resistant ring shank nail.	
Roof Shingles: Asphalt shingles installed throughout the roof deck as per the Florida Building Code HVAZ.	
NanoBit Rafter (Part No. K50065-BK1) Installation: The NanoBit rafter mount was installed over rafters using one 5/16" lag screw with a sealing washer. Roof sealant was applied on the bottom of the NanoBit rafter prior to fastening.	
Method of Conditioning: The roof deck was conditioned for 3 days exposure to outside environment conditions. The roof deck temperature was verified each day with a thermocouple and was maintained above 120°F for six hours each day.	

Interval #	Wind Speed (mph)	Time (min)	Observations	Results
1	35	15	No leak	Passed
2	0	5	No leak	Passed
3	70	15	No leak	Passed
4	0	5	No leak	Passed
5	90	15	No leak	Passed
6	0	5	No leak	Passed
7	110	5	No leak	Passed
8	0	5	No leak	Passed

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Immediately after commencement of interval 1 top side



Immediately after commencement of interval 1 bottom side



30 seconds prior to completion of interval 1 top side



30 seconds prior to completion of interval 1 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.




Immediately after commencement of interval 2 top side



Immediately after commencement of interval 2 bottom side



30 seconds prior to completion of interval 2 top side



30 seconds prior to completion of interval 2 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.




Immediately after commencement of interval 3 top side



Immediately after commencement of interval 3 bottom side



30 seconds prior to completion of interval 3 top side



30 seconds prior to completion of interval 3 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.




Immediately after commencement of interval 4 top side



Immediately after commencement of interval 4 bottom side



30 seconds prior to completion of interval 4 top side



30 seconds prior to completion of interval 4 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Immediately after commencement of interval 5 top side



Immediately after commencement of interval 5 bottom side



30 seconds prior to completion of interval 5 top side



30 seconds prior to completion of interval 5 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Immediately after commencement of interval 6 top side



Immediately after commencement of interval 6 bottom side



30 seconds prior to completion of interval 6 top side



30 seconds prior to completion of interval 6 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.

Immediately after commencement of interval 7 top side



Immediately after commencement of interval 7 bottom side



30 seconds prior to completion of interval 7 top side



30 seconds prior to completion of interval 7 bottom side



THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Immediately after commencement of interval 8 top side



Immediately after commencement of interval 8 bottom side



30 seconds prior to completion of interval 8 top side



30 seconds prior to completion of interval 8 bottom side



Conclusion: The sample tested has passed the Florida Building Code TAS 100(a)-95 with no deviation.

Appendix A: Calibration records

Appendix – B 0.05% Maximum Allowable Leakage Calculations

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



TAS 100 (A) Calibration Records

Appendix A

Technician: Jose Sanchez
Date: 9/19/2023

Temperature: 73.6° F
Barometer Reading: 30.06 inHg

Wind Stream Calibration

Engine RPM: 1200 @ 35 MPH

32.0 (mph)	34.0 (mph)	33.0 (mph)	34.0 (mph)
32.0 (mph)	33.0 (mph)	32.0 (mph)	33.0 (mph)

Engine RPM: 2300 @ 70 MPH

71.0 (mph)	69.0 (mph)	71.0 (mph)	69.0 (mph)
69.0 (mph)	71.0 (mph)	71.0 (mph)	72.0 (mph)

Engine RPM: 3200 @ 90 MPH

90.0 (mph)	88.0 (mph)	91.0 (mph)	92.0 (mph)
92.0 (mph)	90.0 (mph)	91.0 (mph)	89.0 (mph)

Engine RPM: 4100 @ 110 MPH

109.0 (mph)	108.0 (mph)	111.0 (mph)	110.0 (mph)
108.0 (mph)	112.0 (mph)	108.0 (mph)	111.0 (mph)

Engine RPM: 4300 @ 115 MPH

118.0 (mph)	115.0 (mph)	116.0 (mph)	116.0 (mph)
116.0 (mph)	114.0 (mph)	116.0 (mph)	114.0 (mph)

Revised: 6/2/2014

Author Jose Sanchez
Page 1 of 5

Form Number TN 509-27

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



TAS 100 (A) Calibration Records
Wind Stream Calibration

Engine RPM: 4400 @ 120 MPH

119.0(mph)	119.0(mph)	121.0(mph)	121.0(mph)
121.0(mph)	120.0(mph)	122.0(mph)	120.0(mph)

Engine RPM: 4800 @ 125 MPH

125.0(mph)	125.0(mph)	121.0(mph)	125.0(mph)
122.0(mph)	126.0(mph)	126.0(mph)	124.0(mph)

Engine RPM: 4900 @ 130 MPH

130.0(mph)	131.0(mph)	132.0(mph)	131.0(mph)
133.0(mph)	134.0(mph)	132.0(mph)	132.0(mph)

Engine RPM: 5100 @ 135 MPH

135.0(mph)	133.0(mph)	135.0(mph)	133.0(mph)
135.0(mph)	134.0(mph)	133.0(mph)	134.0(mph)

Engine RPM: 5300 @ 140 MPH

141.0(mph)	139.0(mph)	141.0(mph)	143.0(mph)
140.0(mph)	142.0(mph)	139.0(mph)	138.0(mph)

Wind speed (mph) shall not exceed or decrease any more than $\pm 10\%$ of the required wind speed as per TAS 100-95(A) section 7.1.2

Revised: 6/2/2014

Author Jose Sanchez
Page 2 of 5

Form Number IN 509-27

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



TAS 100 (A) Calibration Records

Simulated Rainfall and Flow Meter Calibration

Reading #	Flow meter read out gallon/minute	inches/hour	Allowable Standard Tolerance $\pm 5\%$ of 8.8
1	4.3	8.62	8.36-9.24 in/hr
2	4.3	8.62	8.36-9.24 in/hr
3	4.3	8.62	8.36-9.24 in/hr

Section 7.2.3

Formula:

$$[(\text{Gal}/\text{min}) \times (60 \text{ min}/1 \text{ hr}) \times (231 \text{ in}^3/1 \text{ gal})] / 6912 \text{ in}^2 = \text{inches}/\text{hour}$$

Simulated Rainfall and Flow Meter Calibration

Status- 1 minute filling time

Test Number	Weight of Water Bucket	Weight of Bucket Tare	Weight of Water	Divide	Weight of One Gallon	Gallon/minute Collected	Inches/hour	Allowable Standard Tolerance $\pm 5\%$ of 7.2.3
1	36 lbs	(-) 1.0 lbs	35 lbs	/	8.34 lbs	4.19	8.40	8.19-9.05 in/hr
2	36 lbs	(-) 1.0 lbs	35 lbs	/	8.34 lbs	4.19	8.40	8.38-9.26 in/hr
3	35 lbs	(-) 1.0 lbs	34 lbs	/	8.34 lbs	4.08	8.18	8.38-9.26 in/hr

Section: 7.2.5

Formula:

$$[(\text{inches}^2/6912 \text{ inches}^2)/1 \text{ minute}] \times (60 \text{ minutes}/1 \text{ hour}) = \text{inches}/\text{hour}$$

Note: $231 \text{ in}^3 = 1 \text{ gallon}$

Water Distribution Check

10) 24"x24" Absorptive Cloth Material

#1) 244g	#2) 241g	#3) 251g	#4) 247g	#5) 250g
#6) 242g	#7) 242g	#8) 246g	#9) 247g	#10) 251g

Total of all ten squares= 2461 g

Average of ten squares= 246 g

Revised: 6/2/2014

Author Jose Sanchez
Page 3 of 5

Form Number IN 509-27

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



TAS 100 (A) Calibration Records
Water Distribution Check @ 35 (mph)

Reading #1 Total Weight <u>915g</u> (-) tare <u>246g</u> = <u>669g</u> = <u>0.59 inches/hour</u>	Reading #2 Total Weight <u>936g</u> (-) tare <u>246g</u> = <u>690g</u> = <u>0.61 inches/hour</u>	Reading #3 Total Weight <u>936g</u> (-) tare <u>246g</u> = <u>690g</u> = <u>0.61 inches/hour</u>	Reading #4 Total Weight <u>935g</u> (-) tare <u>246g</u> = <u>689g</u> = <u>0.61 inches/hour</u>
Reading #5 Total Weight <u>924g</u> (-) tare <u>246g</u> = <u>678g</u> = <u>0.60 inches/hour</u>	Reading #6 Total Weight <u>924g</u> (-) tare <u>246g</u> = <u>678g</u> = <u>0.60 inches/hour</u>	Reading #7 Total Weight <u>912g</u> (-) tare <u>246g</u> = <u>666g</u> = <u>0.59 inches/hour</u>	Reading #8 Total Weight <u>952g</u> (-) tare <u>246g</u> = <u>706g</u> = <u>0.62 inches/hour</u>
Reading #9 Total Weight <u>929g</u> (-) tare <u>246g</u> = <u>683g</u> = <u>0.60 inches/hour</u>	Reading #10 Total Weight <u>941g</u> (-) tare <u>246g</u> = <u>695g</u> = <u>0.61 inches/hour</u>	Reading #11 Total Weight <u>929g</u> (-) tare <u>246g</u> = <u>683g</u> = <u>0.60 inches/hour</u>	Reading #12 Total Weight <u>1000g</u> (-) tare <u>246g</u> = <u>754g</u> = <u>0.66 inches/hour</u>

Formula: 7.3.5.1

1 gram = 0.061 inches³

$[(\text{in}^3/576^2) / (\text{hours})] = x (\text{inches/hour})$

Run Time= 0.12 hour

No one particular square shall be greater than or less than $\pm 15\%$ of any other square as per TAS 100(A)-95 Section 7.3.6

Revised: 6/2/2014

Author Jose Sanchez
Page 4 of 5

Form Number IN 509-27

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



TAS 100 (A) Calibration Records
Water Distribution Check @ 70 (mph)

Reading #1 Total Weight <u>1029g</u> (-) tare <u>246g</u> = <u>783g</u> = <u>0.69 inches/hour</u>	Reading #2 Total Weight <u>1020g</u> (-) tare <u>246g</u> = <u>774g</u> = <u>0.68 inches/hour</u>	Reading #3 Total Weight <u>1048g</u> (-) tare <u>246g</u> = <u>804g</u> = <u>0.71 inches/hour</u>	Reading #4 Total Weight <u>1028g</u> (-) tare <u>246g</u> = <u>782g</u> = <u>0.69 inches/hour</u>
Reading #5 Total Weight <u>1044g</u> (-) tare <u>246g</u> = <u>798g</u> = <u>0.70 inches/hour</u>	Reading #6 Total Weight <u>1018g</u> (-) tare <u>246g</u> = <u>772g</u> = <u>0.68 inches/hour</u>	Reading #7 Total Weight <u>1026g</u> (-) tare <u>246g</u> = <u>780g</u> = <u>0.69 inches/hour</u>	Reading #8 Total Weight <u>1042g</u> (-) tare <u>246g</u> = <u>796g</u> = <u>0.70 inches/hour</u>
Reading #9 Total Weight <u>1026g</u> (-) tare <u>246g</u> = <u>780g</u> = <u>0.69 inches/hour</u>	Reading #10 Total Weight <u>1044g</u> (-) tare <u>246g</u> = <u>798g</u> = <u>0.70 inches/hour</u>	Reading #11 Total Weight <u>1049g</u> (-) tare <u>246g</u> = <u>808g</u> = <u>0.71 inches/hour</u>	Reading #12 Total Weight <u>999g</u> (-) tare <u>246g</u> = <u>753g</u> = <u>0.66 inches/hour</u>

Formula: 7.3.5.1

1 gram = 0.061 inches³

$[(\text{in}^3/576^2) / (\text{hours})] = x (\text{inches/hour})$

Run Time = 0.12 hour

No one particular square shall be greater than or less than $\pm 10\%$ of any other square as per TAS 100(A)-95 Section 7.3.7.1

Revised: 6/2/2014

Author Jose Sanchez
Page 5 of 5

Form Number IN 509-27

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.



Appendix B

TAS 100(a)-95 0.05% Maximum Allowable Leakage Calculations

Test Frame Size:

8'-0" by 6'-0" or 6912 inches²

8.8 inches/hour of rain in a 15 minute duration:

(8.8 inches/hour) x (15 minutes) x (1hour/60 minutes) = 2.2 inches

2.2 inches of water sprayed over the test frame:

(6912 inches²) x (2.2 inches) = 15,206.4 inches³ of water

1 inch³ of water or 0.576 ounces of water

(15,206.4 inches³) x (0.576 ounces of water) = 8,758.8 ounces of water

0.05% maximum allowable:

(8,758.8) x (0.05%) = 4.379 ounces of water



Notes

* Designates measurements by laboratory

** as per manufacturer

QAI does not have, nor does it intend to acquire or will acquire, a financial interest in any company manufacturing or distributing products tested or labeled by QAI. QAI is not owned, operated, or controlled by any company manufacturing or distributing products it tests or labels.

Drawings referenced in this document are an integral part of this report, therefore, are required when distributing this test report. Test results obtained represent the actual value of the tested specimens and do not constitute opinion, endorsement, or certification by this laboratory.

REMARKS

This product was tested and is in compliance with the Florida Building Code (2023) TAS 100-23(A) with no deviations.

See Appendix A for the calibration records as indicated in TAS 100-23(A). Total water sprayed was 8.8 inches per hour.

REVISION HISTORY:

12/27/2023: Initial report release

1/18/2024: Added part number per clients request.

*****END REPORT*****

THIS REPORT IS THE CONFIDENTIAL PROPERTY OF THE CLIENT ADDRESSED. THE REPORT MAY ONLY BE REPRODUCED IN FULL. PUBLICATION OF EXTRACTS FROM THIS REPORT IS NOT PERMITTED WITHOUT WRITTEN APPROVAL FROM QAI. ANY LIABILITY ATTACHED THERETO IS LIMITED TO THE FEE CHARGED FOR THE INDIVIDUAL PROJECT FILE REFERENCED. THE RESULTS OF THIS REPORT PERTAIN ONLY TO THE SPECIFIC SAMPLE(S) EVALUATED. UNLESS SPECIFICALLY STATED OR IDENTIFIED OTHERWISE, QAI HAS UNTILIZED A SIMPLE ACCEPTANCE RULE TO MAKE CONFORMITY DECISIONS ON TESTING RESULTS CONTAINED IN THIS REPORT, AS APPLICABLE.

